

TRUCK, UTILITY, 1/4 TON, GS, LANDROVER

FITTING INSTRUCTION PLATE - FRONT WHEEL DRIVE

MODIFICATION INSTRUCTION

REFERENCE:- AG in WM No 17120/5.

NOTE:- This instruction supersedes previous issues, all copies of which will be destroyed. There is no significant change.

SUMMARY

1. This instruction covers the fitting of an instruction plate which details the correct engagement of front wheel drive.

Estimated manhours to perform: 0.5

2. **Priority:** Group 2

3. **Vehicles affected:**

All subject vehicles

4. **Items affected:**

Instrument Panel



5. **Action required:** By RAEME workshops authorised to carry out unit repair or work in accordance with WKSP A 850.

6. **Stores required:** Available through normal channels.

Sec/Cat No	Designation	Qty per Veh
LV7/RU/EME1 VEH G 017-8	PLATE instruction, front wheel drive	1

7. Fit instruction plate to instrument panel above speedometer and ammeter in accordance with fig 1 using existing screws.

TO ENGAGE FRONT WHEEL DRIVE	TO DISENGAGE FRONT WHEEL DRIVE
LOW RATIO: Stop vehicle, engage low ratio	FROM LOW RATIO: Change to high ratio (front wheel drive disengaged automatically)
HIGH RATIO: Depress yellow knob	FROM HIGH RATIO: Stop vehicle, change to lower ratio then back to high ratio



LOCATION: On instrument panel and secured by three existing screws at 6 in centres.

FIG 1 - LAYOUT OF INSTRUCTION PLATE 12 1/2 IN x 1 1/4 IN

E N D